

Tattoo²

T.A.Elektronikk AS

Go badge, print yourself!



Color &
Monochrome
Thermal
Transfer



300 dpi



Single-sided



100 cards



0.25 - 0.76 mm
(10 - 30 mil)



1 year

evolis

www.evolis.com

Compact size, ease of use, core features and cost efficiency. Tattoo² is the best deal for printing plastic cards on a small scale and for mobile applications.

In a few seconds, Tattoo² personalizes in monochrome or colour your pre-printed or blank plastic cards.

With a 300 dpi standard resolution and 'near-to-edge' printing, Tattoo prints pictures, texts, barcodes and logos as required.

Tattoo² is a flexible solution which offers a dual card-feeding mode. Cards can be loaded automatically thanks to the 100-card feeder but you can also use the manual loading mode for on-demand delivery.

It also features a detachable output hopper to collect printed cards.

Sleek and with a contemporary look, Tattoo² is today the most compact plastic card printer in its category.

It squeezes into any location: offices, reception desks, and even shop counters.

Tattoo² fully addresses the specific needs of small organizations that print badges in low volume or just once in a while: sport clubs, SMEs, retail outlets, schools, libraries and local authorities

It is ideal for membership cards, subscription and loyalty cards, badges for visitors and employees and much more.

Go badge, print yourself!

GENERAL SPECIFICATIONS

- Color printing module
- 300 dpi print head (11.8 dots/mm)
- USB connection
- 16 MB RAM
- Detachable feeder with a capacity of 100 cards (0.76 mm or 30 mil)
- Detachable output hopper with a capacity of 15 cards (0.76 mm or 30 mil)
- 1-Button and 4-LED control panel
- Available in Fire red color
- Automatic card thickness adjustment

CARD LOADING MODES

- Automatic with feeder and/or hand-feed

PRINT MODES

- Color dye sublimation and monochrome thermal transfer
- Integrated ribbon saver for monochrome printing

PRINTING SPEED

Personalization throughput will depend on card design and printer settings.

- Color (YMCKO): 40 sec/card¹
- Monochrome: 7 sec/card¹

SUPPORTED PLATFORMS

- Windows™ XP, Server 2003 and Vista 32 & 64 bits

SUPPLIED SOFTWARE

- eMedia Trial - 30 days evaluation

RIBBON TYPES

- 5-panel YMCKO color ribbon - 100 cards/roll
- Monochrome ribbons - up to 600 cards/roll (black, red, green and blue) - up to 500 cards/roll (white, gold and silver)
- BlackWAX monochrome ribbon (for ABS & special varnished plastic cards) - up to 600 cards/roll

OPTIONS / ACCESSORIES

- 100-card additional feeder
- Cleaning kits

WARRANTY

Use Evolis Genuine products for best performance and extended lifespan of your printer.

- Printer, print head: 1 year warranty, unlimited number of passes²



- Card types
- Card format
- Card thickness
- Card feeder capacity
- Card output hopper capacity
- Printer size
- Printer weight
- Connections
- Electrical
- Environmental

- All PVC, Composite PVC cards, PET, ABS¹ & varnished¹ cards
- ISO CR-80 - ISO 7810 (53.98 mm x 85.60 mm - 3.375" x 2.125")
- From 0.25 mm (10 mil)³ to 0.76 mm (30 mil)
- 100 cards (0.76 mm - 30 mil), 300 cards (0.25 mm - 10 mil)
- 15 cards (0.76 mm - 30 mil), 45 cards (0.25 mm - 10 mil)
- Height: 166 mm (6.53") - Length: 290 mm (11.42") / 368 mm (14.49") with the detachable hopper
- Width: 187 mm (7.36")
- 2.4 Kg (5.3 Lbs)
- USB (cable supplied)
- Power supply: 100-240 V AC, 50-60 Hz, 1.5 or 1.8 A
- Printer: 24 V DC, 3 A
- Min/Max operating temperature: 15° / 30°C (59° / 86° F)
- Humidity: 20% to 65% non-condensing
- Min/Max storage temperature: -5° / +70°C (23° / 158° F)
- Storage humidity: 20% to 70% non-condensing
- Operating ventilation: free air



1. Under specific conditions
 2. Subject to observance of specific conditions and use of Evolis Genuine Consumables
 3. 10 mil cards must be used only for monochrome printings



Avd. Sandnes
 T.A. Elektronikk AS
 Gravarsveien 55
 4306 Sandnes
 Tlf.nr.: 51 66 65 17

Avd. Oslo
 T.A. Elektronikk AS
 Trollåsveien 4
 1414 Trollåsen
 Tlf.nr.: 992 85 812

E-mail: post@taelektronikk.no
 Web: www.taelektronikk.no
 Support: 992 85 814
 Faks: 51 67 10 07