

DTM AP380e Label Applicator - Technical Specifications

| | |
|--|--|
| Number of Labels Dispensed per Trigger | 1 or 2 - front and back |
| Speed | 142 mm/s (5.6"/s) or up to 1,500 containers per hour |
| Container Shape | Cylindrical and many tapered |
| Container Diameter | 15 mm - 170 mm (0.6" - 6.7") |
| Container Width | 25.4 mm - 238 mm (1" - 9.4") |
| Container Height | 15 mm - 170 mm (0.6 - 6.7") |
| Label Width | 19 mm - 209 mm (0.75" - 8.25") |
| Label Height | 19 mm - 609.6 mm (0.75" - 24") |
| Supply Roll | Up to 203 mm (8") OD with a 50.8 mm to 76.2 mm (2" to 3") ID wound out, die-cut |
| Label Liner Rewinder | Yes |
| Label Sensor Type | Mechanical sensor |
| Indicator Lights | LED display with built-in up/down counter and saved jobs |
| Controls | Footswitch, Push button, Mode, Recall/Reset, Up, Down |
| Power Requirements | 100 V - 240 V AC (50/60 Hz), 12 V DC, 5.0 A |
| Power Consumption | Idle: 1.6 W Average: 20 W |
| Certifications | UL, UL-C, CE, FCC Class A, RoHS, UKCA |
| Weight | 9.07 kg |
| Dimensions (W x H x D) | 340 mm x 226 mm x 508 mm |
| Gap between Labels | Recommended: 3 mm - 6 mm |
| Label Type | Die cut with or without waste removed; clear labels can be used |
| Liner Thickness | 50,8 µm - 254 µm (smoothness will affect feeding - a liner that is too slippery or too thin will slip through the drive rollers) |
| Label + Adhesive Thickness | 127 µm - 381 µm |
| Wind Direction | Wound out - see copy position chart below (position 3 or 4 for most containers) |
| What's in the Box | DTM AP380e Label Applicator, instructions, universal power supply |
| Warranty | 36 months (after product registration, for devices purchased in EU/EFTA countries and UK) |
| Manufacturer | DTM Print GmbH |

LABEL COPY POSITION CHART

Copy positions 1-4 labels wound out

