




ZX10 FULLY RUGGED TABLET

- Qualcomm® QCS6490, Octa-core Processor
- 10.1" LumiBond display with Getac sunlight readable technology (1,000 nits) and glove-enabled capacitive touchscreen
- Dual hot-swappable batteries for uninterrupted operation
- 6ft drop, MIL-STD-810H and IP66 certified
- Optional 1D/2D imager barcode reader
- Multiple configurations with enterprise-level management tools in a light form factor
- Verified as Android enterprise recommended ⁱ



ZX10 3D demo



SPECIFICATIONS

Generation

G2

Operating System

Android™ 13.0ⁱ

Mobile Computing Platform

Qualcomm® QCS6490, Octa-core 1.9GHz Max. 2.7GHz

Graphics

Qualcomm® Adreno™ 643 GPU

NPU

Qualcomm® Hexagon™ Processor, up to 13 TOPS with 6th Qualcomm AI Engine

Display

10.1" TFT LCD WUXGA (1920 x 1200)

Protection film

1,000 nits LumiBond display with Getac sunlight readable technology

Capacitive multi-touch screen

Storage & Memory

8GB LPDDR5

128GB UFS

Optional: 256GB UFS

Device Button

Power button

4 tablet programmable buttons

Pointing Device

Touchscreen

- Capacitive multi-touch screen

- Optional: Dual mode touchscreen (multi-touch and digitizer)

Audio

Integrated stereo speakers

Integrated dual-array microphone

Expansion Slot

Optional: 1D/2D imager barcode reader

Optional: Smart card reader

Optional: NFCⁱⁱ

I/O Interface

8MP webcam x 1

16MP auto focus rear camera x 1

Audio in/out combo x 1

USB 2.0 (Host) x 1

USB 3.2 Gen 1 Type-C w/ DP & PD x 1

MicroSD x 1

Docking connector x 1

Optional: SIM card slot x 1 (Nano-SIM, 4FF)^x

Optional: RF antenna pass-through for GPS, WWAN and WLAN

Communication Interface

Wi-Fi 6E 802.11ax

Bluetooth (v5.2)ⁱⁱ

Optional: Dedicated L1/L5 GPS^v

Optional: 4G LTE mobile broadband^{iv}

Optional: 5G Sub-6^w

Optional: Dual SIM (Nano-SIM 4FF and e-SIM)^{iv,x}

Security Feature

Kensington lock

Optional: NFCⁱⁱ

Optional: Smart card reader

Power

Li-ion battery (3.88V, typical 4990mAh; min. 4870mAh)

+ Battery bay cover

LifeSupport battery swappable technology

Swappable Battery Options:

1. Battery (3.88V, typical 4990mAh; min. 4870mAh) x 2

2. High capacity battery (3.88V, typical 9980mAh; min. 9740mAh) x 2

Dimension (W x D x H) & Weight

275 x 192 x 17.9mm (10.8" x 7.56" x 0.7")

906g (1.99lbs)^w

Rugged Feature

MIL-STD-810H certified

IP66 certified

Vibration & 6 feet (1.8m) drop resistant^x

Optional: ANSI/UL 121201, CSA C22.2 NO. 213 (Class I, Division 2, Groups A, B, C, D)

Environmental Specification

Temperature^{vii}:

- Operating: -29°C to 63°C / -20°F to 145°F

- Storage: -51°C to 71°C / -60°F to 160°F

Humidity:

- 95% RH, non-condensing

Pre-installed Software

Getac Camera

Getac Input Method

Getac Driving Safety Utility (trial version)

Getac settings and Google applications (Search, Chrome, Gmail, Maps, YouTube, Play, Drive, YouTube music, Google TV, Meet and Photos)

Getac Log Tool

Getac Diagnostic

Getac Monitoring (trial version) agent/SDK

Getac Management (trial version) agent/SDK

Optional software

Getac Driving Safety Utility

Getac Monitoring

Getac Management

Getac OEMConfig

Accessories

Battery (3.88V, typical 4990mAh; min. 4870mAh)

Optional:

Carry bag

Battery (3.88V, typical 4990mAh; min. 4870mAh)

High capacity battery (3.88V, typical 9980mAh; min. 9740mAh)

Multi-Bay charger (Dual-Bay)

Multi-Bay charger (Eight-Bay)

65W USB-C AC adapter

DC-DC vehicle adapter (65W, 11-32VDC)

Digitizer pen with tether

Capacitive stylus with tether

Protection film

Hard handle

Shoulder strap (2-point)

Shoulder harness (4-point; handsfree)

Rotating hand strap with kickstand

Keyboard dock

Vehicle dock^{viii}

Office dock

Bumper-to-Bumper warranty

Accidents can take your equipment out of service when you least expect it, especially in a rugged environment, which can cause costly equipment downtime. That is why Getac has introduced accidental damage as standard under our Bumper-to-Bumper warranty, to help minimize your enterprise IT costs. Bumper-toBumper is your hassle-free guarantee. That means you can depend on us to have your unit back in service within days. Standard 3 years

Standard

3 years Bumper-to-Bumper

ZX10 FULLY RUGGED TABLET

- I. Android enterprise recommended rugged devices deliver a consistent set of features verified by Google with an elevated device baseline, increased security standards and enterprise-focused features and behaviors to meet the needs of users. Google and Android are trademarks of Google LLC.
- II. 13.56MHz contactless NFC (ISO 15693, 14443 A/B, Mifare and Felica™ compliant).
- III. Bluetooth performance and connectable distance may be subject to interference with the environments and performance on client devices, users may be able to reduce effects of interference by minimizing the number of active Bluetooth wireless devices that is operating in the area.
- IV. One physical SIM card slot and one eSIM. Network service may vary depending on local telecommunication providers.
- V. Support GPS, GLONASS, Galileo and BeiDou.
- VI. Weight and dimensions vary from configurations and optional accessories; optional high-capacity batteries add approx. 7.65mm (H), 140g.
- VII. When using AC power, the device operates in temperatures as low as -29°C (-20°F), as tested by an independent third-party laboratory following MIL-STD-810H standards. For battery-only operation, it functions down to -15°C (5°F) with one standard battery, -21°C (-6°F) with two standard batteries, and -29°C (-20°F) with two high-capacity batteries.
- VIII. Gamber Johnson and Havis vehicle docks are e-mark certified.
- IX. Drop test results vary from configurations and optional accessories.
- X. Units with 4G/5G option come with an embedded SIM card slot.

Information provided herewith is for reference only, available specification shall be subjected to quotation by request.

	Vehicle Dock	Office Dock (Pogo)
Microphone	1	1
Audio Output	1	1
DC in Jack	1	1
USB	USB 2.0 x 2	USB 2.0 x 3
LAN	-	1
HDMI	-	1
RF Pass-through	Optional: RF antenna connector x 3 (GPS, WWAN, WLAN)	-
Kensington Lock	-	Kensington Lock x 1

Getac



Getac (UK) Ltd.

Getac House, Stafford Park 12, Telford, Shropshire TF3 3BJ, United Kingdom

Tel : +44 (0) 1952 207 222

Sales-Getac-UK@getac.com |

www.getac.com/en/

Copyright © 2025 Getac Technology Corporation and/or any of its affiliates. All Rights Reserved.

Information provided herewith is for reference only, available specification shall be subjected to quotation by request.