



**ZONE 1/21
CL I / DIV 1**

< IS530.1 >

**Always a step ahead!
The smart and innovative
Zone 1/CI I Div1-smartphone
with the most advanced
technology:**

**First Bluetooth® 5 industrial
smartphone with multifunc-
tional ISM interface, a huge
internal memory 64 GB and
the highest camera resolution
of its class.**

► Please visit our website and you will find more detailed information, as well as an overview of compatible accessories. ► i.safe MOBILE and i.safe MOBILE logo are registered trademarks of i.safe MOBILE GmbH. Android is a trademark of Google Inc. The Android robot is reproduced or modified from work created and shared by Google and used according to terms described in the Creative Commons 3.0 Attribution License. Bluetooth® is a registered trademark of Bluetooth SIG, Inc. worldwide. Wi-Fi® is a registered trademark of the Wi-Fi Alliance. All other trademarks and copyrights are the properties of their respective owners. ► © 2019 by i.safe MOBILE GmbH | All rights reserved. | Misprints, errors and modifications excepted. | 1029MD01REV01_EN_04.2019

TECHNICAL FEATURES



ATEX approval applied for:
EX-Zone 1/21
Ⓢ II 2G Ex ib IIC T4 Gb
Ⓢ II 2D Ex ib IIC T135°C
Db IP6X



IECEx approval applied for:
EX-Zone 1/21
Ex ib IIC T4 Gb
Ex ib IIC T135°C Db IP6X



Approval in North America applied for:
Class I, II, III Division 1
Groups A B C D E F G, T4
Intrinsically Safe



Android™ 9.0



2,4GHz + 5GHz: IEEE
802.11a/ b/g/n/ac/e/k/r/h
with max. 8 connections
hotspot



GSM 850/900/1800/
1900 MHz
WCDMA: UMTS B1/2/4/5/8
LTE-TDD: B38/B39/B40/B41
LTE-FDD: B1/2/3/4/5/7/8/12
with MFBI B13/14/17/20/25/
26/28A/28B/29/30/66
TD-SCDMA: B34/B39



Bluetooth® 5.0



Size: 155 x 80 x 25 mm,
weight: 325 g



External memory
microSD up to 128 GB



2 cameras: 13 MP AF
rear camera and 5 MP
front camera



Qualcomm Snapdragon
SDM660 Octa-Core
Kryo Gold-Quad cores
2.2GHz
Kryo Silver-Quad cores
1.8GHz
4 GB RAM
64 GB internal memory
54 GB accessible



Dual micro SIM



Near Field
Communication



SOS-key for additional
app



Universal, lateral
ISM interface

FURTHER FEATURES



Waterproof: 1 hour
up to 2 m, impervious to
dust and microparticles



Operation range from
-20 °C to 60 °C



Drop-protection,
tested against: vibrations,
shock and extreme
temperatures.



4,5" Gorilla Glass®
3. generation



Usable with gloves



Amplified loudspeaker



3600 mAh battery,
replaceable,
3,8V; 13,68Wh



GPS, A-GPS, Glonass,
A-Glonass, Beidou,
Galileo



Location, gyroscope,
gravity, ambient light,
magnetic- and proximity



Push-To-Talk
PTT ready (third party
application provided)



Loneworker protection
LWP ready (third party
application provided)



Quick charge with
magnetic charging port

CONTENTS

Smartphone, battery, i.safe PROTECTOR 2.0 USB cable, i.safe PROTECTOR 3.0 USB cable, charger, quick start manual and safety instructions