



Smart-Ex 01 / 201 & Ex-Handy 09 / 209

DELIVERING MOBILITY

IN HAZARDOUS AREAS

Enterprise Mobility

LEARN ABOUT THE KEY BENEFITS



Smart-Ex® 01 / 201







EXPLORING MOBILITY

Companies are aware of the capability of mobility solutions and the impact they can have on operations, reducing cost and improving efficiency. Game changing new devices are enabling break-throughs in workforce productivity, data quality and the speed and accuracy of decision making.

The world's first Intrinsically Safe 4G / LTE Smartphone, the system. These devices are unlocked and SIM free, offering a reliable connection to any network worldwide. The 9th generation of the Intrinsically Safe cell phones from ecom certified and approved for use in Zone 1 & DIV 1 incl. Dust Ex-areas.

Intrinsically Safe Smartphone / Featurephone QUALITY CONTROL CONDUCTED IN GERMANY, BASED ON 30 YEARS EXPERIENCE

RANGE OF FUNCTIONS

- SIM lock free
- 4G / LTE cellular network connectivity
- Bluetooth® 4.0 incl. BLE (Bluetooth Low Energy) BLE (30 times faster, 1/100th of power)
- WiFi 802.11 a/b/g/n
- Android[™] 4.4.4 operating system
- 4.0" capacitive multi-touch screen made of extreme shock and scratch resistant Gorilla Glass® 2
- Glove Touch Screen
- High Visibility Display in Direct Sunlight
- Camera (see page 10)

- 4800 mAh Li-Ion battery pack (up to 40 hours talk time)
- Magnetic and waterproof USB 2.0 High Speed connector

ZONE 1 / 21, ZONE 2 / 22

DIV 1 / DIV 2

- Push-to-talk (App solution)
- Lone Worker Protection (App solution)
- Dedicated / programmable hardware buttons
- NFC functionality (only Smart-Ex® 01 / 201)
- Optional Service Level Agreement 3 years (SLA)
- MDM + Google Play Store certified
- FOTA (Firmware over the air)

ANDROID™ -THE MOST POPULAR OPERATING SYSTEM

ANDROID™ 4.4.4 enables this intrinsically safe device to be used in hazardous areas without any compromises, especially when compared to conventional smartphones, for these applications and many more. With the online integration and the use of a variety of applications, the Smart - Ex® 01 & 201 / Ex-Handy 09 & 209 allows an efficiency potential and access to productivity and safety

- Collaborative Working
- Audits & Inspection
- Asset Tracking
- Condition Monitoring

- Process Automation
- Indoor / Outdoor Tracking & Navigation
- Man Down Lone Worker Protection
- Push to talk function



www.ecom-ex.com/apps

Enterprise Mobility




ECOM'S MOBILE WORKER CONCEPT





Swapout





Ensuring accurate data capture and real-time information and decision making

Minimizing costs


Rental/

HaaS

Improve ease of use & customer experience



MOBILE WORKER



GPS/RTLS receiver

Noise-cancelling headset

Mobile device (with optional camera/video)

Level

Health sensor



Know How

Assistance



Smart-Ex®



MAKE ALL THE DIFFERENCE

PUSH-TO-TALK (PTT)

PTT over IP is a service providing group communication like Two-Way Radio communication systems (TETRA, DMR and the classic analogue PMR).

Existing systems can be easily substituted, including DECT systems

Benefits

Individual Call / Group Call / Messages / GPS Tracking / Calls History Including Voice Recording / Order Management System with NFC, QR Code / Status Messages / Data Transfer.



LONE WORKER PROTECTION (LWP)

LWP ready for Mobile Worker 4.0

- Easy to integrate in many partner server systems
- Location based services are available
- Interactions with different Applications at the same time run smoothly
- OTA upgrades running well not only for LWP
- Data interaction between control center and end-user is possible

Smart-Ex® 01 / 201 & Ex-Handy 09 / 209

- The LWP Application is running beside the operating system
- The use of Android Apps reduces costs
- Quad core processor divides all services
- In case of a processor malfunction, 3 backup processors ensure that all services are available instantly

WHY USE ZONE 1 / 21 & DIV 1 DEVICES? DO NOT COMPROMISE ON SAFETY

Safety (employees, assets and environments) is priority number one when carrying any electronic device into environments with potentially explosive atmospheres.

Since even Zone 2 equipment is "only required to be safe under normal operating conditions", any fault could potentially cause an explosion in the presence of an explosive atmosphere. Even turning a device "Off" does not make it safe.

Essentially, only equipment certified for use in Zone 1 / Division 1 areas employ additional safety circuits or factors of safety in the event of potential failure and pass extreme impact and drop tests, climate tests, ageing tests.

Even if considered safe to use in hazardous areas, it does not mean it is intrinsically safe / explosion proof unless:

- 1. The device has the correct rating:
 "Ex ia", "Ex ib" or UL913, FM3610, CSA157 and
- 2. The required certification marking is on the device

Evaluate the risk and check if your mobile devices are intrinsically – you may be surprised and even more your company's safety or insurance maybe compromised.

Also take into consideration that Division 2 and even Zone 2 certified devices should be replaced earlier than Division 1 / Zone 1 devices.

MOBILE DEVICE MANAGEMENT

Mobile device management (MDM) is an industry term relating to the administration of multiple devices which helps in dealing with deploying, securing, monitoring and integrating mobile devices

Features

The main aim for deploying MDM on devices is to optimize the functionality and security of mobile devices within an organisation, while simultaneously protecting the corporate network. Key features for a robust and secure MDM include:

- Enroll, provision, configure and manage devices, individually or by a group over-the air (OTA)
- Restrict users to approved applications only.
- Containering; a secured area for business apps



Smart-Ex®



PREMIUM DATA CAPTURING



SOFTWARE BARCODE SCANNER

The ecom CamScan is a "keyboard wedge" software utility based on Honeywell's SWIFTDECODER Mobile a professional offline barcode decodes software, which uses the integrated front / rear camera to scan barcodes, automatically converting them to human readable text. Triggering the scan is easy - simply press the Scan button added to the on-screen keyboard. Audible and vibration feedback is given when the barcode has been decoded and the decoded barcode data will automatically appear in the data field where you need it.

Choose software scanning for a low to medium frequency scanning, where low light and high motion are not an issue.



If data capture is

proving a challenge and you need a powerful and professional solution, you should turn to the Ident-Ex.

SCAN ENGINE



CamScan Keyboard

for Tab-Ex® 01 & Smart-Ex Series / Ex-Handy 209

ADVANTAGES CAMSCAN SOFTWARE

- Uses integrated front / rear cameras no additional hardware needed
- Fast & accurate decoding of a wide variety of 1D and 2D barcodes (even offline)
- Decodes most dirty/damaged barcodes
- Good performance in both sunlight and poor light conditions

BENEFITS

IDENT-EX SCAN HANDLE

connectivity

without limits



ADVANTAGES OF IDENT-EX

- (100 + scans per hour)
- Best for motion tolerance
- Long distance scanning
- RFID



	SMART-EX® 01	SMART-EX® 201	EX-HANDY 09	EX-HANDY 209
Operating System	Android 4.4.4			
Chipset	MSM8926 1.2 GHz Quad core			
Band	4G / LTE-Standard Quad Band UMTS 850 / 900 / 1900 / 2100 MHz Quad Band GSM 850 / 900 / 1800 / 1900 MHz EU: B1, B3, B7, B8, B20, B38 (TDD) US: B1, B2, B3, B4, B5, B7, B8, B12, B17			
Antenna	MIMO antenna for LTE			
WiFi	802.11 a / b / g / n dual-band, WiFi Direct, WiFiHotspot			
Memory	16 GB Internal Storage / 1GB RAM		8 GB Internal Storage / 1GB RAM	
User memory	12 GB		4 GB	
Applications	Google Play Store certified			
CONNECTIVITY				
Bluetooth SMS, MMS	BT4.0 / BLE (Low Energy)			
(text, image, audio, video)	Support SMS and MMS			
GPS, NFC	GPS, GLONASS, NFC		GPS, GLONASS	
Email Client	EAS, Gmail, POP3, IMAP			
Capacity (mAh)	3600 mAh 4800 mAh		3600 mAh	4800 mAh
Battery Life	Up to 1000 hours Stand by, up to 40 hours talk time			
PHYSICAL CHARACTERISTICS				
Ambient temperature	-20°C+55°C			
Protection class	IP68			
Size	137 x 72.1 x 26.9 mm (5.39"x 2.54"x 1,05")	137 x 72.1 x 20.8 mm (5.39 x 2.54 x 0,82")	137 x 72.1 x 26.9 mm (5.39"x 2.54"x 1,05")	137 x 72.1 x 20.5 mm (5.39 x 2.54 x 0,80")
Weight	approx. 370 g	approx. 290 g	approx. 330 g	арргох. 270 g
Dedicated Keys	PTT key / Alarm key / Power key			
Ports	3.5 mm audio connector			

CERTIFICATION					
	SMART-EX® 01	SMART-EX® 201	EX-HANDY 09	EX-HANDY 209	
ATEX	© II 2G Ex ib IIC T4 Gb IP64 © II 2D Ex ib IIIC T135 °C Db IP64	© II 3G Ex ic IIC T4 Gc IP64 © II 3D Ex ic IIIB T135 °C Dc IP64	© II 2G Ex ib IIC T4 Gb IP64 © II 2D Ex ib IIIC T135 °C Db IP64	© II 3G Ex ic IIC T4 Gc IP64 © II 3D Ex ic IIIB T135 °C Dc IP64	
IECEX	Ex ib IIC T4 Gb IP64 Ex ib IIIC T135 °C Db IP64	Ex ic IIC T4 Gc IP64 Ex ic IIIB T135 °C Dc IP64	Ex ib IIC T4 Gb IP64 Ex ib IIIC T135 °C Db IP64	Ex ic IIC T4 Gc IP64 Ex ic IIIB T135 °C Dc IP64	
NEC & CEC	Class I, Division 1, Groups A-D T4 Class II & III, Division 1, Groups E-G T4	Class I, Division 2, Groups A, B, C, D, T4	Class I, II, III Division 1 Groups AG T4	Class I, Division 2, Groups A,B,C,D, T4	



	SMART-EX® 01	SMART-EX® 201	EX-HANDY 09	EX-HANDY 209
DISPLAY				
Size	4.0 inch		2.6 inch	
Туре	Corning Gorilla® Glass 2 with Glove Touch, Blanview Display			
Audio				
Microphone	Dual Mic Solution with Noise cancellation			
Speaker	19 mm Loud Speaker with Gore® Protective Vents, Output up to 103 dB			
MULTIMEDIA				
Camera	8 MP auto focus rear,	1MP fixed focus front	-	5 MP auto focus rear
LED torch light	Yes			

SCOPE OF DELIVERY SMART-EX® / EX-HANDY

- Smart-Ex® 01 & Smart-Ex® 201 Safety Box SB S01 / Ex-Handy 09 / 209
- Li-Ion battery 3600mAh (built-in) Belt Clip BC S01 / S201 / H09 / H209 Li-Ion battery 4800mAh (built-in)
- Charger TC S01
- USB data cable PC S201
- Needle (for opening SIM Slot)
- Documentation



Find more on www.ecom-ex.com

ACCESSORIES SMART-EX® & EX-HANDY

BELT CLIP	LEATHER CASE	LEATHER HOLSTER

COMPATIBLE WITH

3M TM PELTOR TM WS TM ProTac XP Ex	EX-RSM AURELIS BT SPEAKERMIC	SMART MUFF	COM COM EX	SERENITY SPC
		.	-6	



EMEA

Germany (Headquarters) 1

ecom instruments GmbH Industriestraße 2 97959 Assamstadt Phone +49 62 94 42 24-0 Fax +49 62 94 42 24-100 sales@ecom-ex.com

ecom Benelux 2

ecom instruments BV
Watertoren 45c
3247 CL Dirksland, Netherlands
Phone +31 1 87 60 59 16
Fax +31 1 87 60 33 47
info.nl@ecom-ex.com
²also covering Belgium and Luxemburg

France ³

ecom Nied sarl
4 Rue Ettore Bugatti
67201 Eckbolsheim
Phone +33 3 88 76 46 84
Fax +33 3 88 76 02 85
info.fr@ecom-ex.com
3 also covering Algeria, Egypt, Morocco,
Tunisia and Libya

Italy

ecom instruments srl Via Gandhi, 15 Galleria 20017 Rho (MI) Phone +39 02 93 90 92 16 Fax +39 02 93 90 62 97 info.it@ecom-ex.com

Switzerland

ecom instruments GmbH Merkurstraße 2 6210 Sursee Phone +41 4 19 21 60 00 Fax +41 4 19 22 00 08 info.ch@ecom-ex.com

Nordics

ecom instruments GmbH Postbox 304 2970 Hørsholm Denmark Phone +45 28 252 575 info.nordics@ecom-ex.com

United Kingdom

ecom instruments ltd A310, The Wilton Centre, Redcar, TS10 4RF, United Kingdom Phone +44 1642 46 54 00 Fax +44 1642 46 54 02 info.uk@ecom-ex.com

Middle East

ecom instruments fze P.O. Box 8918 Saif-Zone, Sharjah, UAE Phone +971 6 5 57 34 30 Fax +971 6 5 57 34 31 info.uae@ecom-ex.com

Americas

USA

ecom instruments Inc. 1779 Westborough Drive, Suite 102 Katy, Texas 77449 Phone +1 281 496 59 30 Fax +1 281 496 23 21 info.us@ecom-ex.com

Asia

South East Asia

ecom instruments (SEA) Pte Ltd.
12 Arumugam Road
#05-11 Lion Building B
Singapore 409958
Phone +65 61 00 33 29
Fax +65 63 99 33 29
info.sg@ecom-ex.com

