



IP66

K120 FULLY RUGGED TABLET

- 11th Generation Intel[®] Core[™] i7 / i5 vPro[™] Processor
- 12.5" FHD LumiBond[®] 2.0 Display with Getac Sunlight Readable Technology (1,200 nits) and Capacitive Touchscreen
- Enhanced Enterprise Security with optional Intel vPro, Windows Hello face-authentication camera, and multi-factor authentication options
- Multi-mode usage streamlined by extensive accessory selections
- LifeSupport[™] Battery Swappable Technology
- Thunderbolt[™] 4 brings lightning speed and performance



Rugged Mobile Computing Solutions

Specifications

Generation G2

Operating System Windows 10 Pro

Mobile Computing Platform Intel® Core[™] i5-1135G7 Processor Max. 4.2GHz with Intel® Turbo Boost Technology - 8MB Intel® Smart Cache - SMB Intel® Smart Cache Platform Options: Intel® Core³⁴ i5-1145G7 vPro³⁴ Processor Max. 4.4GHz with Intel® Turbo Boost Technology - SMB Intel® Smart Cache Intel® Core³⁴ i7-1165G7 Processor Max. 4.7GHz with Intel® Turbo Boost Technology - 12MB Intel® Smart Cache Intel® Core™ i7-1185G7 vPro™ Processor Max. 4.8GHz with Intel® Turbo Boost Technology - 12MB Intel® Smart Cache

VGA Controller Intel[®] Iris[®] X^e Graphics

Display 12.5" IPS TFT LCD FHD (1920 x 1080) Protection film 1200 nits LumiBond® display with Getac sunlight readable Capacitive multi-touch screen

Storage & Memory 16GB DDR4 Optional: 32GB DDR4

256GB PCIe NVMe SSD Optional: 512GB / 1TB PCIe NVMe SSD Keyboard

Power button 5 tablet programmable buttons **Pointing Device**

Touchscreen

Capacitive multi-touch screen Optional: Dual mode touchscreen (multi-touch and digitizer)

Expansion Slot Optional: 1D / 2D imager barcode reader Optional: Serial port (9-pin; D-sub), or USB 2.0 port I/O Interface

I/O Interface Tablet: FHD webcam x 1* 8M pixels auto focus rear camera x 1 Headphone out / mic-in combo x 1 DC in Jack x 1 USB 3.2 Gen 2 Type-A x 1 Thunderbolt[™] 4 x 1 LAN (RH45) x 1 HDMI x 1 Docking connector x 2 Optional: Windows Hello face-authentication camera (front-facing) x 1* RF antenna pass-through for GPS, WLAN and WWAN Obtional Kevboard Dock: Optional Keyboard Dock: DC in Jack x 1 USB 3.2 Gen 1 Type-A x 3 LAN (RJ45) x 1

HDMI x1 HDMI x1 Display Port 1.2 x 1 Serial port (9-pin; D-sub) x 1 Optional: RF antenna pass-through for GPS, WLAN and WWAN

Communication Interface

Intel® Wi-Fi 6 AX201, 802.11ax 10/100/1000 base-T Ethernet Bluetooth (v5.2) Optional: Dedicated GPS^{vii} Optional: 4G LTE mobile broadband with integrated GPS^{vii}

Security Feature

TPM 2.0 Kensington Lock Optional: Intel[®] vPro[™] Technology Optional: Smart Card reader or HF RFID reader^{ii, iii} or fingerprint reader[®]

Power

AC adapter (90W, 100-240VAC, 50 / 60Hz) Li-lon smart battery (11.1V, typical 2100mAh; min. 2040mAh) x 2 LifeSupport[™] battery swappable technology Optional: High capacity battery (14.4V, typical 3450mAh; min. 3300mAh) x 2 **Dimension (W x D x H) & Weight**

Tablet: 329.5 x 238 x 24 mm (12.97" x 9.37" x 0.94") 1.7Kg (3.75lbs)^v Tablet+Optional Keyboard Dock: 340.5 x 307.5 x 47 mm (13.40" x 12.10" x 1.85") 3.13Kg (6.9lbs)^v

Rugged Feature

MIL-STD-810H certified IP66 certified MIL-STD-461G certified⁴⁴ Vibration & 6 feet (1.8m) drop resistant^{441, 1X} e-Mark certified for vehicle usage Optional: ANSI / UL 121201, CSA C22.2 NO. 213⁴⁴¹

Environmental Specification

Temperature^{ix} Operating: -29°C to 63°C / -20°F to 145°F Storage: -51°C to 71°C / -60°F to 160°F Humidity: - 95% RH , non-condensing

Pre-installed Software

Getac Utility Getac Camera Getac Geolocation Getac Barcode Manager^{xi} Optional: Absolute Persistence®

Accessories Battery (11.1V, typical 2100mAh; min. 2040mAh) AC Adapter (90W, 100-240VAC) Capacitive Stylus Optional: Carry Bag Battery (11.1V, typical 2100mAh; min. 2040mAh) High Capacity Battery (14.4V, typical 3450mAh; min. 3300mAh) Multi-Bay Charger (Dual Bay) Multi-Bay Charger (Dual Bay) AC Adapter (90W, 100-240VAC) Office Dock AC Adapter (120W, 100-240VAC) MIL-STD-461 Certified AC Adapter (90W, 115-230VAC) Vehicle Adapter (120W, 11-32VDC) Diatizer Pen Optional: Digitizer Pen Capacitive Stylus Protection Film Tablet Hard Handle

Hand Strap Shoulder Strap (2-point) Shoulder Harness (4-point; handsfree) Keyboard Dock Vehicle Dock Office Dock Spare SSD Kit

Bumper-to-Bumper Warranty

Accidents can take your equipment out of service when you least expect it, especially in a rugged environment, which can cause costly equipment downtime.

That is why Getac has introduced accidental damage as standard under our Bumper-to-Bumper warranty, to help minimize your enterprise IT costs. Bumper-to-Bumper is your hassle-free guarantee. That means you can depend on us to have your unit back in service within days. Standard

3 years Bumper-to-Bumper

- Bluetooth performance and connectable distance may be subject to interference with the environments and performance on client devices, users may be able to reduce effects of interference by minimizing the number of active Bluetooth wireless devices that is
- operating in the area. 13.56MHz Contactless HF RFID / NFC reader (ISO 15693, 14443 A/B, Mifare and FeliCa™
- compliant). iii LF/HF RFID reader option is not Energy Star 8.0 compliant. Smart card reader, HF RFID reader and
- Smart card reader, HF KFID reader and fingerprint scanner are mutually exclusive options. Weight and dimensions vary from configurations and optional accessories; optional high capacity batteries add approx. 11 mm (H), 0.20 kg. MIL-STD-461G 90W AC adapter sold separately. Available with limited configurations. vi
- vii
- viii Drop test results vary from configurations and optional accessories.
- Tested by an independent third-party test lab following MIL-STD-810H. FHD webcam and optional Windows Hello Х
- face-authentication camera (front-facing) are mutually exclusive options. Available when barcode reader option is selected.
- xii Dedicated GPS is mutually exclusive with 4G LTE mobile broadband. Supports GPS and

K120 Fully Rugged **Tablet**



Docking Solutions

| | Vehicle Dock for Tablet Mode | Vehicle Dock for Laptop Mode | Office Dock for Tablet Mode | Office Dock for Laptop Mode |
|-------------------------|------------------------------------|------------------------------------|-----------------------------------|-----------------------------------|
| Serial Port | 1 | 1 | 1 | 1 |
| VGA | 1 | 1 | 1 | 1 |
| Microphone | | | 1 | 1 |
| Audio Output | | | 1 | 1 |
| DC in Jack | 1 | 1 | 1 | 1 |
| USB | USB 2.0 x 3 USB 3.2 Gen1 x 3 | USB 2.0 x 3 USB 3.2 Gen1 x 3 | USB 2.0 x 2 USB 3.2 Gen1 x 3 | USB 2.0 x 2 USB 3.2 Gen1 x 3 |
| LAN | 2 | 2 | 2 | 2 |
| HDMI | 1 | 1 | 1 | 1 |
| RF Antenna Connector | 3 (WWAN, WLAN, GPS) | 3 (WWAN, WLAN, GPS) | | |
| Kensington Lock | 1 | 1 | 1 | 1 |



Getac (UK) Ltd.

Getac House, Stafford Park 12, Telford, Shropshire TF3 3BJ, United Kingdom Tel : +44 (0) 1952 207 222 Sales-Getac-UK@getac.com | www.getac.com/en/



Copyright © 2021 Getac Technology Corporation and/or any of its affiliates. All Rights Reserved tion provided herewith is for reference only available specification shall be subjected to quotation by request. V01M04Y21UK